

Hydrite® PXNLC

Product Description

Hydrite® PXNLC is a low conductivity hydrous kaolin providing edge protection in solvent and water based industrial coating applications.

Application

- Architectural Coatings
- Coil Coatings
- Electrodeposition Coatings
- Industrial primers & topcoats

IMERYS Kaolin

100 Mansell Court East
Suite 300, Roswell, GA 30076
United States
Tel: +1 (770) 594 0660

Customer Service:

Tel: +1 (888) 567 6548
Fax: +1 (770) 645 3685
www.imerys-kaolin.com

IMERYS is a business name of
IMERYS Pigments, Inc.,
IMERYS Kaolin, Inc. and
IMERYS Marble, Inc.
Registered in the USA

©IMERYS 2016
Tenth Edition, July 2015
CAS No. 92704-41-1

TYPICAL PROPERTIES

Physical Form	Pulverised Powder	
Brightness	(GE, % of MgO)	88.5
Particle Size	(Sedigraph) (µm)	0.4
Screen Residue	(325 mesh screen, wt.%)	0.03
Hegman		5
Oil Absorption	(g/100g)	42
pH	(20% solids)	4.5
Free Moisture	(wt. %)	1.0
Specific Gravity		2.58
Surface Area	(B.E.T. Nitrogen, m ² /g)	12
Weight per Gallon	(lbs)	21.7
Refractive Index		1.56

ISO9001
CERTIFIED

The data quoted here is believed to be correct. Every precaution is taken to ensure the products conform to our published data, but since the products are based on naturally occurring raw materials, we reserve the right to change these data should it become necessary. All recommendations and sales are made on the condition that we will not be held liable for any damages resulting from their use. This provision may not be changed by any of our representatives.